

**LOW-VELOCITY SPALL TESTING OF TI-6AL-4V ALLOY
AND NEW SPALL CRITERION BASED ON MESOSCALE**

First interim Report
(June.17/2002 – Sept.16/2002)

Principal Investigator: J.R.KLEPACZKO

**UNITED STATES ARMY EUROPEAN RESEARCH OFFICE
LONDON, UK**

CONTRACT N°: N62558-02-M-5857
R8D 9314-AN-01

Contractor:

Laboratory of Physics and Mechanics of Materials
ISGMP, UMR – CNRS 7554
METZ UNIVERSITY
F-57045 Metz, France

Approved for public release
Distribution unlimited

20030306 108

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204 Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE June 17 / 2002	3. REPORT TYPE AND DATES COVERED First Interim Report, June 17 / 2002 – September 16 / 2002		
4. TITLE AND SUBTITLE LOW-VELOCITY SPALL TESTING OF TI-6Al-4V ALLOY AND NEW SPALL CRITERIUM BASED ON MESOSCALE			5. FUNDING NUMBERS C-N62558-02-M-5857	
6. AUTHOR(S) J.R. KLEPACZKO				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) METZ UNIVERSITY – ISGMP LAB. OF PHYSICS AND MECHANICS OF MATERIALS ILE DU SAULCY, F-57045 METZ cedex 1, FRANCE			8. PERFORMING ORGANIZATION REPORT NUMBER N/A	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) USA RDSG-UK, AERONAUTICS AND MECHANICS BRANCH Dr. Sam SAMPATH 223 OLD MARYLBONE RD. LONDON NW1-5TH, U.K.			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT DISTRIBUTION UNLIMITED			12b. DISTRIBUTION CODE N/A	
13. ABSTRACT (Maximum 200 words) This Interim Report covers the contract period from June 17/2002 to Sept.16/2002 (the first period of three months).The research in this Project is directed toward better understanding of the development of the local plastic fields occurring in mesoscale during spalling of Ti-6Al-4V alloy. The specimens in the form of disks of different thickness and DIA 57.0 mm have been delivered by AMSRL-WM-TA, APG Aberdeen, MD. Later, all specimens have been polished and measured in our Laboratory (LPM). The plate-plate facility is in the stage of preparation. Since an observation on mesoscale is envisaged, more exactly, the surface topography after spall fracture will be analyzed, two new high resolution profilometers, one based on the light interferometry: WYKO NT1000 by VEECO and the second: MAHR profilometer, based on mechanical contact, have been put into operation. Both profilometers are equipped with a software which has been already tested . The software permits for a detailed analysis of 3D profiles. Preliminary analyses of the spall surfaces available after earlier experiments are in progress. The test results obtained for Ti-6Al-4V from experiments of shearing at high strain rates will be applied to identification of material constants in new temperature coupled constitutive relation.				
14. SUBJECTS ITEMS TITANIUM ALLOY TI-6Al-4V LOW-VELOCITY SPALL, SPALL CRITERION			15. NUMBER OF PAGES 03	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT	

NSN 7540-01-280-5500

Standard Form 298 (Rev.2-89)
Prescribed by ANSI Std. Z39-18
298-102

EXTENDED ABSTRACT

During the first period (three months from June 17/2002 to Sept. 16/2002) of the Contract the experimental program was setup to test Ti-6Al-4V alloy by so called plate-plate impact technique. The main purpose of this study is to clarify, using spall experiments, the role of short-time local plastic fields occurring in the meso-scale. The thermal coupling and the local high strain rates will be considered in the modeling.

The Laboratory of Physics and Mechanics of Materials is equipped, besides Hopkinson bars in compression and torsion, in the plate impact facility with bore diameter 57 mm. A flyer plate can be accelerated up to 800 m/s depending on the gas that is used. A series of spall tests are planned with different target/flyer thickness. A critical minimal impact velocity will be sought when the incipient spall occurs at loading times from ~ 600 ns to ~ 2.5 μ s. The specimens in the form of disks of different thickness and DIA 57 mm have been delivered by AMSRL-WM-TA, APG Aberdeen, MD. The plate impact facility is in the stage of preparation, including an automatic procedure of the launching.

Since an observation of the spalled surfaces is envisaged, more exactly the surface topography in 3D, two new high resolution profilometers, one based on the light interferometry (laser interference): WYKO NT1000 by VEECO, and the second: MAHR Profilometer, based on mechanical contact, have been put into operation. Both profilometers are equipped in a sophisticated software which has been already tested. The software permits for a detailed analysis of the surface profiles in 3D including statistics. Preliminary analysis of the spall surfaces available after previous tests are in progress.

After previous projects on Ti-6Al-4V supported by the European Research Office of the US Army an ample data are available obtained in fast shearing which will permit to identify all material constants in a constitutive relation developed in LPMM.

During last years, within the framework of the previous projects on spall mechanics, advances in understanding fracture in the meso-scale are quite obvious. A review of fracture criteria will permit to make a correct choice for the Finite Element codes, [1]. Studies on mechanical and microstructural aspects of spall have provided further data on armor steels and hard aluminum alloy, [2,3]. A new model of spall fracture will be developed for Ti-6Al-4V based on the plate impact experiments, microscopic observations and topography analysis.

References

- [1] P.Chevrier and J.R.Klepaczko, Discussion of fracture criteria in spall mechanics, Eng. Trans., **45** (1997), 47.
- [2] P.Chevrier and J.R.Klepaczko, Spall fracture, mechanical and microstructural aspects, Eng. Fract. Mech., **63** (1999), 273.
- [3] J.R.Klepaczko and P.Chevrier, Fracture dynamics in one-dimensional strain, in: Modeling of Damage and Fracture Processes in Engineering Materials, IFTR, Warsaw, Poland, (1999), 90.

Research reported in this document has been made possible through the support and sponsorship of the US Government through its European Research Office of the US Army. This Interim Report is intended only for the internal management use of the Contractor and the US Government.